

DPT145 Multiparameter transmitter for SF6 gas

		1	2	3	4	5	6	7	8	9	10	11	PRICE
Vaisala Multiparameter Transmitter		DPT145	A			A	A					A	
1	Probe	DPT145 base - probe with UNF 7/8- 14 thread											
2	Measurement parameters	Td/f, Td/f atm, ppm, P, Pnorm, density and T for SF6 gas											
		Td/f, Td/f atm, ppm, P, Pnorm, density and T for mixed SF6/N2 gas, %SF6 _____ %N2 _____											
3	Digital output	RS-485											
		RS-485 with Modbus RTU mode by default											
4,5	Reserved codes												
6	Output units	Metric units (Celsius, bara)											
		Non-metric units (Fahrenheit, psia)											
7	Mechanical connection	<i>DIL0 DN8 connector</i>											
		<i>DIL0 DN20 connector</i>											
		<i>ABB connector</i>											
		<i>Alstom connector</i>											
8	Cable for RS485 output and power supply	None											
		<i>1,5 m Shielded PUR cable with 90°connector</i>											
		<i>3 m Shielded PUR cable with 90°connector</i>											
		<i>5 m Shielded PUR cable with 90°connector</i>											
		<i>10 m Shielded PUR cable with 90°connector</i>											
		<i>3 m Shielded FEP cable with straight connector (Compatible w. combination of Alstom connector + Rain shield)</i>											
		<i>15 m Shielded PUR cable with straight connector</i>											
		<i>20 m Shielded PUR cable with straight connector</i>											
9	Installation accessories	None											
		<i>Weather shield</i>											
10	Special features	None											
11	User's guide	None											
		Multilingual quick guide											
Total													
Total value													

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

DPT145 **A** **1** **A** **A** **A** **1** **B** **1** **1** **A** **X**

End customer: _____

Accessories and spare parts

219980	Connection cable for DM70
219690	USB Serial Interface Cable
218675SP	Protection plug for connector
231519SP	1.5 m Shielded PUR cable with 90°connector
231520SP	3 m Shielded PUR cable with 90°connector
231521SP	5 m Shielded PUR cable with 90°connector
231522SP	10 m Shielded PUR cable with 90°connector
226902SP	3 m Shielded FEP cable with straight connector
236407SP	15 m Shielded PUR cable with straight connector
235859SP	20 m Shielded PUR cable with straight connector
ASM210326SP	Weather shield

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd.
NO.32,ShuPing Road, Jiading District, ZIP201808,
Shanghai R.P.China
TEL: 0086 21 6630 8161/62/63
FAX: 0086 21 6630 8167