

For wall mounting

*) Note! Simultaneous installation of LAN and Universal AC-power is possible only with a short cable probe.

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT330	1	A	0	B	1	0	1	B	C	A	B	1	0	0	A	1	A	A	B	A	A	1
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

End customer:

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd
NO.32,ShuPing Road, JiadingDistrict,ZIP201808,
Shanghai R.P.China
TEL: 0086 21 6630 8161/62/63
FAX: 0086 21 6630 8167

HMT333 Humidity and Temperature Transmitter

For general use

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT330	3	0																				1	PRICE
1	Transmitter type	HMT333	3																						
2	Cable length	2 m cable, +80 °C 5 m cable, +80 °C 10 m cable, +80 °C 20 m cable, +80 °C 2 m cable, +120 °C 5 m cable, +120 °C 10 m cable, +120 °C	E F G Q 4 5 6																						
3	No additional temperature probe		0																						
4	Parameters	RH+T+Td+Td+a+x+Tw+ppm+pw+pws+h+dT	B																						
5	Display	No display Graphical display with keypad	0 1																						
6	Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC-power (100...240 VAC) Universal AC-power (100...240 VAC) + US power cord Universal AC-power (100...240 VAC) + EUR power cord Universal AC-power (100...240 VAC) + UK power cord Universal AC-power (100...240 VAC) + AUS power cord External US AC-adaptor (for LAN/WLAN interface in USA and Canada) Not IP65	0 1 2 3 4 5 6 9																						
7	Signal output	Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) + Serial interface RS232 or optional communication module	4... 20 mA 0... 20 mA 0... 1 V 0... 5 V 0... 10 V	1 2 3 4 5																					
8	Analog output signals	No 3rd analog output																							
9	for Ch1, Ch2 and Ch3	RH (0... 100%RH) T (range: see below) Td (-20...100 °C) (-4...+212 °F) TdF (-20...100 °C) (-4...+212 °F) a (0...600g/m3) (0...262 gr/ft3) Tw (0...100 °C) (+32...+212 °F) x (0...500g/kg d.a) (0...3500gr/lb) h (-40...1500 kJ/kg) (-9.5...+652.6 Btu/lb) ppm (0...5000) pw (0...1000 hPa) (0...14.5psi) pws (0...1000 hPa) (0...14.5psi) dT (-10...+50 °C) (14...+122 °F)	B C D E F G H J K L M N X	B B C C D D E E F F G G H H J J K K L L M M N N X X X X																					
10	SPECIAL Define quantity Define scale	Ch1: _____ Ch2: _____ Optional Ch3: _____ Channel 1 Channel 2 Channel 3, choose A if not needed																							
11	Analog output range for temperature - Choose option A, if no T output is desired	No temperature output -40...+60 °C (-40...+140 °F) -40...+80 °C (-40...+176 °F) -40...+120 °C (-40...+248 °F) -20...+60 °C (-4...+140 °F) -20...+80 °C (-4...+176 °F) -20...+120 °C (-4...+248 °F) 0...+60 °C (+32...+140 °F) 0...+100 °C (+32...+212 °F) 0...+120 °C (+32...+248 °F) special : _____	A B C C D D F F G G H H K K L L M M X X																						
12	Output units	Metric Non-metric	1 2																						
13	Option for module slot 1	No module Relay output RS-485 serial interface (galvanically isolated) LAN (Ethernet) interface + 2 m cable (RJ45) Data logger module	0 1 2 4 6																						
14	Option for module slot 2	No module Relay output 3rd Analog output Choose also analog output signal for Ch3 Data logger module Not possible if the data logger module has already been chosen in item 13	0 1 3 6																						
15	Cable bushings Note: The Universal AC power not connected through 8-pole connector!	Cable gland M20 x 1.5 Conduit fitting NPT1/2" 8-pole connector with 5m cable spare cable: 212142 8-pole counter connector equipped with screw terminals spare connector: 212416 Bushing Set (Cable gland M20 x 1.5 and Conduit fitting NPT1/2")	A B C D G																						
16	Transmitter installation	Normal mounting Wall mounting plate item: 214829 Pole installation kit item: 215108 Pole installation kit with rain shield item: 215109 DIN rail kit item: 215094	0 1 2 3 4																						
17	Humidity sensor type	General purpose and high chemical concentrations with chemical purge function Catalytic humicap sensor with chemical purge HUMICAP180R spare: HUMICAP180R HUMICAP180RC spare: HUMICAP180RC HUMICAP180VC spare: HUMICAP180VC	A C K																						
18	Sensor protection	PPS plastic grid & stainless steel netting PPS plastic grid Sintered stainless steel filter spare: DRW010281SP spare: DRW010276SP spare: HM47280SP	A B C																						
19	Installation kit for probe	No kit Duct installation kit item: 210697 Cable gland AGRO M20 x 1.5 with split seal item: HMP247CG	A C D																						
20	Operating manual language	No manual English German French Finnish Swedish Spanish Japanese Russian Chinese	A B C D E F G J K V																						
21	PC Accessories	No Service cable for PC, RS232 (D9 female connector) item: 19446ZZ MI70LINK software for Windows® with RS232 service cable item: 215005 Service cable for PC, USB item: 219685 MI70LINK software for Windows® with USB service cable item: 219916	A B C D E																						
22	Calibration	ISO9001 compliant factory calibration Special calibration service item for calibration: RH/CALSTD see separate order form	A X																						
23	Additional maintenance	No maintenance and repair contract	1																						

TOTAL
QTY
TOTAL VALUE

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT330 3 E 0 B 1 0 1 B C A F 1 0 0 A 0 A A A B A A 1

End customer:

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd.
NO.32,ShuPing Road, JiadingDistrict,ZIP201808,
Shanghai R.P.China

TEL: 0086 21 6630 8161/62/63

FAX: 0086 21 6630 8167

For high humidities

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT330	7	S	0	B	1	0	1	B	C	A	B	1	0	0	A	0	A	A	A	B	A	A	1
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

End customer:

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd.
NO.32,ShuPing Road, Jiading District, ZIP 201808,
Shanghai R.P.China

TEL: 0086 21 6630 8161/62/63

FAX: 0086 21 6630 8167

HMT338 Humidity and Temperature Transmitter

For pressurized pipelines

			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT338	8	0																						1 PRICE
1 Transmitter type	HMT338		8																							
2 Cable length	2 m cable for 232 mm probe 5 m cable for 232 mm probe 10 m cable for 232 mm probe 2 m cable for 454 mm probe 5 m cable for 454 mm probe 10 m cable for 454 mm probe 20 m cable for 454 mm probe	V W X 1 2 3 9																								
3 No additional temperature probe		0																								
4 Parameters	RH+T+Td+Tdf+a+x+Tw+ppm+pw+pws+h+dT	B																								
5 Display	No display Graphical display with keypad	0 1																								
6 Power supply	10...35 VDC, 24 VAC 10...35 VDC, 24 VAC with galvanic isolation Universal AC-power (100...240 VAC) Universal AC-power (100...240 VAC) + US power cord Universal AC-power (100...240 VAC) + EUR power cord Universal AC-power (100...240 VAC) + UK power cord Universal AC-power (100...240 VAC) + AUS power cord External US AC-adaptor (for LAN/WLAN interface in USA and Canada) Not IP65	0 1 2 3 4 5 6 9																								
7 Signal output	Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) Analog output channel (Ch1&Ch2&Ch3) + Serial interface RS232 or optional communication module	4... 20 mA 0... 20 mA 0... 1 V 0... 5 V 0... 10 V	1 2 3 4 5																							
8 Analog output signals 9 for Ch1, Ch2 and Ch3	No 3rd analog output RH T Td (-20...100 °C) Tdf (-20...100 °C) a (0...600g/m3) Tw (0...100 °C) x (0...500g/kg d.a.) h (-40...1500 kJ/kg) ppm (0...5000) pw (0...1000 hPa) pws (0...1000 hPa) dT (-10...+50 °C) SPECIAL Define quantity Define scale	(0... 100%RH) (range: see below) (-4...+212 °F) (-4...+212 °F) (0...262 gr/ft3) (+32...+212 °F) (0...3500gr/lb) (-9.5...+652.6 Btu/lb) (0...5000) (0...14.5psi) (0...14.5psi) (14...+122 °F) Ch1: Ch2: Optional Ch3: Ch1: Ch2: Optional Ch3: Channel 1 Channel 2 Channel 3, choose A, if not needed	A B B C C C D D D E E E F F F G G G H H H J J J K K K L L L M M M N N N X X X																							
11 Analog output range for temperature	No temperature output -40...+60 °C -40...+80 °C -40...+120 °C -40...+180 °C -20...+60 °C -20...+80 °C -20...+120 °C -20...+180 °C 0...+60 °C 0...+100 °C 0...+120 °C 0...+180 °C -60...60 °C Special	(-40...+140 °F) (-40...+176 °F) (-40...+248 °F) (-40...+356 °F) (-4...+140 °F) (-4...+176 °F) (-4...+248 °F) (-4...+356 °F) (+32...+140 °F) (+32...+ 212 °F) (+32...248 °F) (+32...356 °F) (+32...356 °F) (-76...+140 °F) :	A B C D E F G H J K L M N P X																							
12 Output units	Metric Non-metric	1 2																								
13 Option for module slot 1	No module Relay output RS-485 serial interface (galvanically isolated) LAN (Ethernet) interface + 2 m cable (RJ45) Data logger module	0 1 2 4 6																								
14 Option for module slot 2	No module Relay output 3rd Analog output Data logger module	0 1 3 6																								
15 Cable bushings	Cable gland M20 x 1.5 Conduit fitting NPT1/2" Note: The Universal AC power not connected through 8-pole connector! 8-pole connector with 5m cable 8-pole counter connector equipped with screw terminals Bushing Set (Cable gland M20 x 1.5 and Conduit fitting NPT1/2")	A B C D G																								
16 Transmitter installation	Normal mounting Wall mounting plate Pole installation kit Pole installation kit with rain shield DIN rail kit	0 1 2 3 4																								
17 Humidity sensor type	General purpose and high chemical concentrations with chemical purge function Catalytic humicap sensor with chemical purge	HUMICAP180R HUMICAP180RC HUMICAP180VC	item: 214829 item: 215108 item: 215109 item: 215094																							
18 Sensor protection	PPS plastic grid & stainless steel netting PPS plastic grid Sintered stainless steel filter Stainless steel grid	spare: HUMICAP180R spare: HUMICAP180RC spare: HUMICAP180VC	A C K																							
19 Installation kit for probe	Ball valve set (ISO 1/2") Pressure fitting NPT 1/2" Pressure fitting ISO 1/2"	item: DRW010281SP item: DRW010276SP item: HM47280SP item: HM47453SP item: BALLVALVE-1	A B C D																							
20 Operating manual language	No manual English German French Finnish Swedish Spanish Japanese Russian Chinese	A B C D E F G H J K V																								
21 PC Accessories	No Service cable for PC, RS232 (D9 female connector) MI70LINK software for Windows® with RS232 service cable Service cable for PC, USB MI70LINK software for Windows® with USB service cable	item: 19446ZZ item: 215005 item: 219685 item: 219916	A B C D E																							
22 Calibration	ISO9001 compliant factory calibration Special calibration	service item for calibration: 216989 see separate order form	A X																							
23 Additional maintenance	No maintenance and repair contract																									
		TOTAL																								
		QTY																								
		TOTAL VALUE																								

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT338 | 8 | V | 0 | B | 1 | 0 | 1 | B | C | A | B | 1 | 0 | 0 | A | 0 | A | A | B | A | A | 1

End customer:

上海博众测量技术有限公司

Bodhi (Shanghai) measurement technology Co.,Ltd.

NO.32,ShuPing Road, Jiading District, ZIP201808,

Shanghai R.P.China

TEL: 0086 21 6630 8161/62/63

FAX: 0086 21 6630 8167